

COMPACT FLATWORK IRONERS

S1000-2600

S1000-3300

FEATURES

These flatwork ironers are available in 2 working width: 2m60 and 3m30 and 3 types of heating: electric, gas or steam. They are specially designed for the hospitals and hotels laundries where great quantity of linen should be handle in a shortest time possible.

S models are the less complex ironers that dry and iron without any folding devices.




- Roll sizes: 2m60 and 3m30 wide and 1000 mm diameter.
- One or two working lanes : one lane for bedsheets and two lanes for tablecloths and small pieces.
- Frequency inverter.
- Feeding and ironing by Nomex quality belts.
- Panels in white painted steel.
- Polished steel roll with fingers guard.
- Touch screen control: programs can be created with speed control (between 4 and 18 m/min) and temperature.
- Big output capacity: depending on the residual moisture of the linen, up to 290 kg/h straight from a high spin washer extractor.
- Electric, gas or steam heating
- Two versions of gas heated models:
 - gas with atmospheric burners,
 - gas with radiant burners
- **25 % gas consumption savings and 25 % more production**
- Powerful exhaust system

OPTIONS

- Vacuum feeding belts
- Automatic 1 lane clamp feeder with vacuum feeding belts
- Rear exit
- Motorized rear exit - height 850 mm (rear exit included)
- Small pieces back collector 2 lanes + by-pass included
- Small pieces back collector 4 lanes + by-pass included
- Special voltage

TECHNICAL DATA	UNIT.	S1000-2600	S1000-3300
GENERAL DETAILS			
Theoretical production (45%) humidity	Kg/h	190-230	250-290
Ø Roll	mm	1.000	1.000
Working width	mm	2.600	3.300
Height floor-feeding	mm	1.050	1.050
Working speed	mt/min	4-18	4-18
Control type	-	Touch	Touch
POWER			
Heating power (electric model)	kW	90	90
Total electric power (electric model)	kW	92,6	92,6
Heating power (gas model)	kW	117	156
Total electric power (gas model)	kW	2,6	2,6
Heating power (steam model)	kW	120	150
Total electric power (steam model)	kW	2,6	2,6
CONNECTIONS			
Ø Gas inlet	BSP	1"	1"
Ø Steam inlet	BSP	1-1/4"	1-1/4"
Ø Condensed (Steam model)	BSP	1"	1"
Ø Air inlet	mm	12	12
DIMENSIONS / PACKAGING DIMENSIONS			
Width / Width	mm	3.786 / 3.870	4.486 / 4.570
Depth / Depth	mm	1.985 / 2.070	1.985 / 2.070
Height / Height	mm	2.180 / 2.380	2.180 / 2.380
Weight / Weight	Kg	3.100 / 3.550	3.700 / 4.250
Volume	m3	16,38 / 19,07	19,41 / 22,51
OTHERS			
No. Fume outlet	Nº	2	2
Ø Fume outlet	mm	120	120
Air flow	m3/h	2 x 1.000	2 x 1.000
Air Consumption (6,5 Bar)	NI/h	5.000	5.000
Sound Level	dB	70	70



- A. Compressed air
- C. Condensation discharge (steam heating)
- E. Electrical connection
- F. Fumes discharge connection
- G. Gas inlet (gas heating)
- V. Steam inlet (steam heating)

	H	I	T	S	A	C	E	F	G	V
S1000-2600	2.166	3.242	186	152	Ø 12	1"	5 x 2,5	Ø 120	1"	1-1/4"
S1000-3300	2.166	3.942	186	152	Ø 12	1"	5 x 2,5	Ø 120	1"	1-1/4"